# Priority One Mobility

ECONOMY CLASS SCOOTER WITH
GREAT OUTDOOR STABILITY
AND IMPRESSIVE FEATURES

Pathrider® ES 10

## PATHRIDER® ES 10

The **Pathrider® ES 10** delivers great outdoor stability, ease of use and maximum value. Features include a bright headlight, adjustable tiller and stylish design.

Pride®
Mobility Products
Australia Pty. Ltd.
— LIVE YOUR BEST® —

Tel. 03 6424 5414 | www.priorityonemobility.com.au

# Pathrider® ES 10 4-wheel

| | |
|---|---|
| Weight capacity: | 158 kg (350 lbs.) |
| Maximum speed[1]: | Up to 8.8 km/h (5.5 mph) |
| Ground clearance[2]: | 8.89 cm (3.5”) (at midframe) |
| Overall length[2]: | 119.4 cm (47”) |
| Overall width[2]: | 57.15 cm (22.5”) |
| Turning radius: | 132.08 cm (52”) (left) |
| Range per-charge[1,6]: | 17.92 km (11 miles) (with U-1 batteries) |
| Tyre size: | Front: 10 cm x 25.4 cm (4” x 10”) solid<br>Rear: 10 cm x 25.4 cm (4” x 10”) solid |
| Total weight without batteries[2,7]: | 52.3 kg (115.5 lbs.) |
| Heaviest piece when disassembled[2]: | Front: 25.8 kg (57 lbs.) |
| Standard seating: | Type: Foldable molded plastic<br>Weight: 9.75 kg (21.5 lbs.)<br>Material: Black vinyl<br>Dimensions: 45.72 cm (18”) overall width<br>43.18 cm (17”) effective depth |
| Seat-to-deck range: | 44.5 cm - 48.3 cm (17.5” - 19”) |
| Drivetrain: | Rear-wheel drive, sealed transaxle, 24-volt DC motor |
| Dual braking system: | Regenerative and electromechanical |
| Battery requirements[3,4]: | Two 12-volt, deep cycle<br>Size: U-1 (30 - 34 AH)<br>Weight: 11 kg (24.5 lbs.) each |
| Battery charger: | 3-amp, off-board |

Colours:

Red

## Features

- Disassembles for transport or storage
- Backlit battery gauge
- Bright LED headlight
- Seat features viscoelastic foam inserts for increased comfort and slider for enhanced positioning
- Adjustable tiller
- 158 kg (350 lbs.) weight capacity

## Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Weather cover
- Saddlebag

[1] Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of (+ or -) 10%.

[2] Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3%.

[3] AGM or gel cell type required.

[4] Battery weight may vary based on manufacturer.

[5] Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4, and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

[6] Includes standard seat weight.

The information contained herein is correct at the time of publication; due to Pride’s commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

Quality System
Quality Endorsed Company
ISO 9001 QEC20029
SAI Global

Pride® Mobility Products Australia Pty. Ltd.

P: 03 6424 5414
E: priorityonemobility@bigpond.com
**priorityonemobility.com.au**

PRIDE PERFORMANCE MOBILITY — LIVE YOUR BEST®